

DIN-Rail Mount, Central Time Clock and Main Automation Controller. It is the smart system servant that assist and monitor temperature, events, energy consumption, patterns, with main Targets: maintain, safeguard, protect and economize. It Can Trigger prayer announcements, reminders, alerts, macros, and moods. Each Logic module Consist of 240 tables, Each Table of 4 programmable Logic Lines totaling up to 960 Line of Logics using simplified (and, Or Nand, Nor, with 255 Flags). logical condition consist of trigger combinations like: time, scene Light channel status, curtain status, room temperature, security mode, day night, time... and so on
 **Added function: Improved Logic Table Configuration and Viewing of used against available flags.

technical data



Time Clock

Built in time clock with central Broadcast function.
 DTS day time adjustment
 Muslim 5 Prayer Times function according to city Long and Lat.

Logic Lines

Total 960 logic lines: 240 Tables, each 4 Logic lines.

Logic Commands

Simplified logic commands like: (if, or, nand, nor +255 Flags)

Control IO

3 x Advanced RS485 S-BUS serial port links (both train & screw link types)

Upgrade IO

1 x mini USB port (to connect to special programming board)

User Controls

• LED status indicator/channel
 • Diagnostic LED+ BROADCAST

Programming

• Advanced Software Configuration & Programming

Compliance

CE Mark EMC

Operation Protection

• BUS Rv. Polarity Protection
 • BUS Short Circuit Protection

Trigger Conditions

Logical trigger or command conditions consist of trigger combinations like: time, scene Light channel status, curtain status, room temperature, security mode, day, night, flag...etc.

SBUS DC Supply

24VDC with flexible tolerance between 8-32VDC. Flexible ability to add power supply as to be needed any where
 Power consumption: 15mA

Installation

• 35mm DIN-Rail Mount Ready
 • Wall Mount Ready (4P)

Operating Environment

0° to 45°C ambient temperature
 20% to 93% RH

Enclosure & Size

Polycarbonate, DIN-rail (4 Unit)


Dimensions & Weight

W 91mm x L 73mm x H 75mm
 Packed weight 0.22 kg

control compatibility



- Lighting
- Music
- Curtains
- Moods
- Security
- Service
- Color
- Drapes
- Pumps
- Gates

connection diagram




S-BUS MESH Network


mounting dimensions



ELEVATION




PROSPECTIVE



SIDE VIEW

S-BUS connection



UTP core colors **SES**

S-BUS 24+V		orange
S-BUS GND		w/orange
S-BUS D+		blue
S-BUS D-		w/blue
Spare		green
Spare		w/green
Spare 12+v		brown
Spare 12-V		W/brown